



GR3
GR6

- Full-power control over-current protection mechanism.
- Due to short circuit protection mechanism, rapid response, turn off output power.
- Unique output pressure limit is set to ensure that the amplifier does not appear square wave signal.

SPECIFICATIONS

MODEL	GR3	GR6
Stereo (2 Channels)	Power	Power
8Ω / FTC 20Hz-20kHz @ 0.5% THD	2x200W	2x600W
4Ω / FTC 20Hz-20kHz @ 0.5% THD	2x300W	2x800W
S/N (20Hz-20KHz) 8Ω	95dB	
THD (@8Ω 1KHz)	<0.5%	
Input Impedance	20KΩ	
Frequency Response	20Hz-20KHz	
Circuit Type	CLASS H	
Damping Factor	>500 @8Ω	
Cooling System	2Fans	
In/Output Connection	Input: Balance Female XLR, Link out: Phoenix plug	
Control	Volume Control for each channel. Stereo Denote, Parallel Denote, Low cut	
Indicator light	POW:ACTIVE, SIG:SIGNAL, PRO:PROTECT, CLIP	
Protection	Short, Auto Limited, Overload, AC/DC protection	
Dimension (W x D x H)	555 x 470 x 140mm	
Power Supply	220V (Default), 110V (Could be customized)	

GR3
GR6

