

PRODUCT SPECIFICATION SHEET

TYPE	L-2TDA	PART NO.	32A250001
SPEC.	(28/0.10BC+1/1X1HN)X1.5mmX2C+(pvc/red, white)+20 Cotton yarn+14AF+(96/0.09BC) Braid+PVC6.0		
STANDARD	Refer to Q/FDXL1-2016 factory wire structure standard		

CONSTRUCTION

CONDUCTOR	CONSTRUCTION	28/0.10BC+1/1X1HN bare copper stranded wire (BC OFC)		
	DC RESISTANCES (MAX. at 20°C)	82.700/km		
INSULATION	MATERIAL / COLOUR	PVC (polyethylene) / RED, WHITE		
	DIAMETER / THICKNESS	1.5±0.20 mm / 0.40 0.34 mm		
FILLER	MATERIAL	COTTON YAM		
DRAIN WIRE	CONSTRUCTION	/		
WRAP	MATERIAL	ALUMINUM FOIL		
SHIELD	CONSTRUCTION	96/0.09BC bare copper braid (TC OFC)		
	COVERAGE	0.65		
	DC RESISTANCES 电阻 (MAX. at 20°C)	28.21 Ω/km		
COVERING	MATERIAL / COLOUR	/		
	DIAMETER / THICKNESS	/		
JACKET	MATERIAL / COLOUR	PVC / BLACK		
	DIAMETER / THICKNESS	6.0±0.20 mm / 1.30 1.10mm		
MARKING	DIVA AUDIO PROFESSIONAL 1.Diva Audio 2.High Performance OFC Professional Microphone Cable 3.Meter Mark			
LENGTH	100M		WEIGHT 100m KG	5.2±0.2
PACKING	WOODEN SHAFT			

PERFORMNCE

CAPACITANCE BETWEEN CONDUCTORS pF/m	65	RTED TEMPERATURE °C	-20 / 70
CAPACITANCE BETWEEN CONDUCTORS/SCREENS	130	OPERATING VOITAGE AC / DC V	DC 15
CHARACTERISTIC IMPEDANCE Ω	85	WITHSTAND VOLTAGE (KV AC/MIN)	0.5
DRAWING			