

BYOM-HD 4K HDMI Button Sender

Featured with HDMI Sender & USB Camera Receiver

HDMI Wireless Sender Technical Specification

Port	HDMI X 1 Audio / Video Input
Devices Supported	Windows PC & Mac Computer
Software	No Software Installation required Hardware Encoded
Receiver Supported	BYOM-09, BYOM-09L
Video Resolution	3840X2160, 2560x1600, 1920x1200, 1920x1080, 1366x768, 1280x800, 1280x720, 1024x768
Max Resolution	Up to 3840x2160 fps 30
Codec	H.265, H.264
Audio Encode	44.1KHz/48KHz/16bit PCM, Stereo

USB Camera Receiving Specification

Port	Type USB X 1 Output Camera Video
OS Support	Windows PC & Mac Computer
Software Installation Required	No, Standard UVC&UAC Port
Cloud Meeting App	Zoom、Microsoft Teams、Google Meet, Skype
Playback App	WIN10/11 Camera Playback App MAC QuickTime App PortPlayer , OBS



USB Camera Receiving Specification

SnapShow BYOM Receiver	BYOM-09, BYOM-09L
UVC Resolution	1920X1080, 1280x720
UVC Codec & Frame Rate	MJPEG, 30 fps
UAC Output	Mono, Stereo, 8~48KHz

Hardware Specification

Port	USB Type C x 1 Power Supply, Pairing, Upgrade, Camera Audio & Video Receiving
Antenna	2T2R, Build in Antenna
Wireless Connecting	Auto run once plug in WIFI Auto Connecting, One Click away sharing WIFI Embedded, No PC WIFI required
IEEE protocol	IEEE 802.11ac/802.11n
Transmission Distance	Visual Distance 30 M
WIFI	5G & 2.4G
WLAN Frequency	2.4 GHz (2400 - 2500 MHz) 5.2 GHz (5150 - 5350 MHz) 5.8 GHz (5725 - 5850 MHz)
Encryption	WPA2-PSK
Connecting Time	< 13 Second
Transmission Latency	<150mS
Touch Panel Back Control	Win PC 10 Points Back Control
Power Consumption	5V/1A, Average 3.0W
Size	64mm x 63mm x 20mm
Temperature	Operation: +5°C ~ +40°C; Storage: -20°C ~ +60°C
Humidity	Operation & Storage : 0 ~ 90%