

## School Digital Amplifier

### SA-60D

| Model                  | SA-60D                                                                                                                                                |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Source           | 220 – 240 V AC, 50/60 Hz                                                                                                                              |
| Rated Output           | 60 W                                                                                                                                                  |
| Power Consumption      | 100 W (rated output), 18 W (EN60065)                                                                                                                  |
| Frequency Response     | 20 Hz – 20 kHz                                                                                                                                        |
| Distortion             | 1 % or less                                                                                                                                           |
| Input                  | MIC 1, 2: -52 dB*, 600 $\Omega$ , unbalanced, $\phi$ 6.3 phone jack (2P)<br>AUX 1, 2: -20 dB*, 10 k $\Omega$ , unbalanced, RCA pin jack               |
| Output                 | Speaker out: Low impedance (2 x 8 $\Omega$ or 1 x 4 $\Omega$ ), Push-in terminal                                                                      |
| Protection             | Power Supply Thermal Shut down<br>Power Amplifier Thermal Shut down<br>Power Amplifier Over Current<br>Each protection will be restored automatically |
| S/N Ratio              | MIC 1, 2: 60 dB or more<br>AUX 1, 2: 70 dB or more                                                                                                    |
| Indicator              | Power LED (Blue)                                                                                                                                      |
| Operating Temperature  | 0 °C to +40 °C                                                                                                                                        |
| Operating Humidity     | 90 %RH or less (no condensation)                                                                                                                      |
| Finish                 | Case: Steel plate, off-white, paint / Knob: ABS resin, black                                                                                          |
| Dimensions (W x H x D) | 210 x 70.6 x 180 mm                                                                                                                                   |
| Weight                 | 1.6 kg                                                                                                                                                |
| Accessory              | Wall mounting pattern paper x 1                                                                                                                       |

