

ADP-DAI-1X0

Order No. 0259650



SMART
HOME
READY Dante®

Dante® AVIO analogue input adapter (1-channel)

- For connecting analogue audio line level devices (e.g. mixer) to a Dante® audio network
- Adjustable signal level: +24/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 20 kΩ (bal.), 10 kΩ (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB



- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR inline jack

ADP-DAI-2X0

Order No. 0259660



SMART
HOME
READY Dante®

Dante® AVIO analogue input adapter (2-channel)

- For connecting analogue audio line level devices (e.g. mixer) to a Dante® audio network
- Adjustable signal level: +24/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 20 kΩ (bal.), 10 kΩ (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB



- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR inline jack

ADP-DAO-0X1

Order No. 0259670



SMART
HOME
READY Dante®

Dante® analogue output adapter (1-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 kΩ (bal.), 75 kΩ (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB



- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR plug

ADP-DAO-0X2

Order No. 0259680



SMART
HOME
READY Dante®

Dante® analogue output adapter (2-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 kΩ (bal.), 75 kΩ (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB



- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR plug

ADP-USB-2X2

Order No. 0259690



SMART
HOME
READY Dante®

Dante® AVIO USB adapter

- For connecting a computer to a Dante® audio network
- 2-channel recording/reproduction
- Sampling rate: 48 kHz
- Compatible with Windows, Mac OS, iOS and Android devices, no drivers required
- Connections: 1 x RJ45, 1 x USB Type-A



ADP-AES3-2X2

Order No. 0259640



SMART
HOME
READY Dante®

Dante® AVIO AES3/EBU adapter

- For connecting analogue devices with AES3/EBU interface to a Dante® audio network
- Impedance: 110 Ω (bal.)
- S/N ratio: > 135 dB
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR plug, 1 x XLR inline jack



TPE-TG80G

Order No. 0069200



Gigabit Power over Ethernet switch

- 8 ports (RJ45) with 10/100/1,000 Mbps each, 8 PoE/PoE+ ports
- Bandwidth: 16 Gbps
- Power per port: 30 W (PoE+), 15.4 W (PoE)
- Total power of PoE: 105 W
- Compatible with standards IEEE802.3 10BaseT, IEEE802.3u 100BaseTX, IEEE802.3ab 1000BaseT, IEEE802.3at, IEEE802.3af, IEEE802.3x, IEEE802.3az
- Metal housing



- Power is provided via enclosed power supply
- Admissible ambient temperature: 0-40 °C
- Dimensions: 142 x 30 x 95 mm
- Weight: 400 g

TPE-TG44G

Order No. 0069190



Gigabit Power over Ethernet switch

- 8 ports (RJ45) with 10/100/1,000 Mbps each, 4 of which PoE/PoE+ ports
- Bandwidth: 16 Gbps
- Power per port: 30 W (PoE+, 2 ports max.), 15.4 W (PoE, 4 ports max.)
- Total power of PoE: 60 W
- Compatible with standards IEEE802.3 10BaseT, IEEE802.3u 100BaseTX, IEEE802.3ab 1000BaseT, IEEE802.3at, IEEE802.3af, IEEE802.3x, IEEE802.3az
- Metal housing



- Power is provided via enclosed power supply
- Admissible ambient temperature: 0-40 °C
- Dimensions: 142 x 30 x 95 mm
- Weight: 380 g