

Building Automated System Cables

BAS Cable 1P No Shield - Speaker Cable

APPLICATIONS :

- BUILDING SOUND, BROADCAST, AUDIO AND INSTRUMENT
- REMOTE CONTROL OF AUTOMATIC ELECTRICAL EQUIPMENT ex. RECORDING & RELAYING DEVICES LIFT, LIGHT AND AIR CON. SYSTEM VOLTAGE CONTROL SYSTEM OTHER COMMONLY UTILIZED FOR IN PROCESS CONTROL

PRODUCT DESCRIPTION :

CONDUCTOR

- 22 THRU 12 AWG STRANDED TINNED COPPER

INSULATION

- COLOR CODED PE INSULATION, BLACK & CLEAR

JACKET

- PVC GREY JACKET

TEMP.RATING

- -20 TO +75 °C

MAX. VOLTAGE

- 300 V RMS



UL file no.E135928

Part No.	No. of Pairs	Nominal Conductor		Nominal Insulation thickness		Drain wire	Jacket thick	Nom. OD.	Nominal Capacitance	
		AWG	(No./mm.)	inch	mm.	Size	mm.	mm.	pf/ft	pf/m
P/N9122	1	22	7/0.254	0.02	0.41	22	0.64	4.40	24	47
P/N9120	1	20	10/0.254	0.02	0.41	20	0.71	5.10	27	49
P/N9118	1	18	16/0.254	0.02	0.46	20	0.71	5.60	24	44
P/N9116	1	16	26/0.254	0.03	0.81	18	0.81	7.80	23	44
P/N9114	1	14	42/0.254	0.03	0.81	16	0.89	8.60	24	47
P/N9112	1	12	65/0.254	0.04	0.94	12	1.02	10.10	25	49

