



AVIO-A-2OUT-EB



Order No.: 1001505

PRODUCTINFOS

Professional Dante® audio output for fixed installations

The AVIO-A-2OUT-EB, a 2-channel analogue output adapter that reliably transmits Dante® audio signals to analogue end devices, is specially designed for the installation market. With Euroblock connections, PoE supply and a sophisticated mounting system, this adapter is perfect for AV integrators, system houses and installation companies.

Dante® AVIO analogue output adapter (2-channel)

- Euroblock outputs for fast and secure hardwiring
- Compatible with Dante®, automatic network detection, plug-and-play
- PoE power supply (802.3af Class 1), no separate power supply unit required
- Adjustable output level: +4/0 dBu/0/-10 dBV (via Dante® controller)
- Frequency range 20-20,000 Hz
- Impedance 20 kΩ (bal.), 10 kΩ (unbal.)
- Sample rate 44.1/48/96 kHz, 16/24/32 Bit
- Dante® AVIO ClickGrid system allows the combination of multiple adapters for structured installations
- Easy to install, supplied with bracket for rack, table or wall mounting

Common applications:

- Conference rooms and meeting areas
- Educational facilities and lecture theatres
- Houses of worship and event rooms
- Stage, zone and area distribution for event venues

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Manufacturer information:

Audinate Ltd.
Future Business Centre
Kings Hedges Rd
Cambridge CB4 2HY
United Kingdom
info@audinate.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

AVIO-A-2OUT-EB

Description	Dante® AVIO analogue output adapter
Type	2-channel
Colour	black
Power supply	PoE
Admiss. ambient temp.	-10 °C to +45 °C
Weight	145 g
Connections	1 x RJ45, 1 x 6-pole Euroblock, 3.5 mm
Packing unit	1
Packaging dimensions (W x H x L)	0.19 x 0.0925 x 0.045 m

AVIO-A-2OUT-EB

Gross weight 0.206 kg

Net weight 0.145 kg

AVIO-A-2OUT-EB

EAN code 9353345000107

Net weight 0.145 kg

AVIO-A-2OUT-EB

Sampling rates 44.1/48/96 kHz

Resolution 16/24/32 bit