

HY-6530D

Digital Touch Delegate Conference Microphone

Description

- Uses the advanced and stable "IRIN" chip and DSP/DDOV digital conference technology to achieve digital signal transmission and processing
- Built-in high-fidelity 9.7mm gold-plated capacitive microphone capsule, precisely calculating aperture and spacing, effectively improving vocal frequency response range and pickup sensitivity
- Unique cavity and microphone design combined with interference correction technology to precisely control pickup details, accurately controlling pickup angle and avoiding acoustic feedback and howling
- High-sensitivity design with built-in automatic gain control (AGC) function, effective pickup distance up to 50-60cm
- Uses FTC334C professional capacitive touch key processing chip, virtual touch keys with no mechanical key noise when switching on/off, ensuring long service life
- Adopts a desktop streamlined design, embedded with steel mesh, glass or acrylic, and metal lines, featuring a modern technological feel
- Equipped with a 2" LCD high-brightness display and a 6" large capacitive touch panel, capable of displaying system ID, speaking time, and other information
- Features speech timing and timed speaking functions, supports dynamic display of speaking time, and allows setting of countdown time for speaking
- Uses high-fidelity lossless audio transmission technology, supports 48KHz audio sampling frequency, sensitive pickup, clear voice, with frequency response up to 20Hz-20KHz
- Microphone rod joints and all studs are made of pure copper to restore sound quality, ensure stable quality, and guarantee pickup distance and sound quality
- Uses high-quality sponge covers with good elasticity, breathability, and anti-loosening functions, which are not easy to fall off or deform during use
- Equipped with intelligent audio detection function, automatically inverts and attenuates audio when two adjacent units are close to prevent howling
- Supports "ring hand-in-hand" connection, comes with professional 8-core or CAT5 cables, with full aluminum foil and water line shielding to effectively prevent electromagnetic interference
- Supports eight meeting modes: quantity limit, first-in-first-out, last-in-first-out, chairman permission (request to speak), voice-activated start, timed speaking, queue speaking, and free discussion
- The number of speakers can be set from 1 to 20, with no limit for chairman and VIP units; free discussion mode has no limit on the number of speakers and can be fully opened

Specifications

Mechanical	
Microphone capsule type	9.7mm gold-plated capsule
Polar pattern	Cardioid electret
Display	2" LCD display
Frequency response	20Hz-20KHz
Sensitivity	-37dB±2dB
Output impedance	<200Ω
Maximum sound pressure level	125dB (1% T.H.D. 1kHz, 0dB SPL=2x10Pa)
Signal-to-noise ratio	>90dB
Dynamic range	>96dB
Equivalent noise level	18dB, A-weighted
Connection method	T-head, splitter box
Headphone output interface	Φ3.5mm stereo jack
Connection cable	8-core DIN interface or RJ45 interface (optional)
Power supply	DC24V host power supply
Microphone rod size	390mm
Base size	166×125×52mm (excluding microphone rod)

All Information Copyright 2026 (HUAIN)